

Product Photos

High Contrast Ratio with Black Face LEDs





Product Features

Light weight and slim design, low power consumption and wide viewing angles.

- 7.5kgs /cabinet, 30kgs/sqm, (include power supply and receiving card)
- Cabinet size : 500mm(w)*500mm(h)=0.25m²
- Module size : 250mm(w)*250mm(h)
- **The widest portion is less than 72mm**
- **The thinnest portion is 25mm**

Product Features

It can stand on the floor easily and stably, so this cabinet is suitable for both of standing structure and hanging structure

When you use the hanging structure, the hook on the bottom of cabinet can help you to install the screen more easily and conveniently



Specification

Pixel pitch	4.81mm (SMD3528)	Color temperature	6500k
Size of cabinet	500mm*500mm	Control method	Synchronization
Pixel of cabinet	104*104	Driving device	Constant current
Weight of cabinet	<9KGS	Driving method	1/ 13 scanning
Size of module	250mm*250mm	Frame frequency	> 60Hz
Resolution of module	52*52	Refresh frequency	>2400HZ
Density	43264dot/M2	Brightness	>1500cd/M2
Best viewing distance	>4M	Working voltage	AC220v/110v±10%
Best viewing angle	≤140 degree	Working temperature	-20 ~50℃±10%
Max power consumption	<750w/sqm	I P grade	IP43
Colors	16777216	MTBF	10,000hours
Gray scale	14bits	Life span	100,000hours

The above parameters are only for reference and can be changed upon customer's requests.